

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A47K 10/42, 10/44		A1	(11) International Publication Number: WO 98/22009 (43) International Publication Date: 28 May 1998 (28.05.98)
(21) International Application Number: PCT/US97/21373 (22) International Filing Date: 21 November 1997 (21.11.97) (30) Priority Data: 08/755,435 22 November 1996 (22.11.96) US (71) Applicant: KIMBERLY-CLARK WORLDWIDE, INC. [US/US]; 401 North Lake Street, Neenah, WI 54956 (US). (72) Inventors: CHAN, Michael, Yuwah; 10435 Stanyan Street, Alpharetta, GA 30202 (US). TRAMONTINA, Paul, Francis; 155 Cobblestone Way, Alpharetta, GA 30201 (US). (74) Agents: SIDOR, Karl, V. et al.; Kimberly-Clark Worldwide, Inc., 401 North Lake Street, Neenah, WI 54956 (US).			(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>

(54) Title: **INTERFOLDED NAPKIN DISPENSING SYSTEM**

(57) Abstract

An interfolded paper napkin dispensing system composed of : a) an outer housing (12) defining an interior space (14); b) stacking means (16) mounted within the outer housing (12) for holding a stack of paper napkins (18) within the interior space (14); and c) a dispensing face (20) defined in the outer housing (12) proximate to an end of the stacking means (16). The dispensing face (20) has a central portion (22) projecting out from the dispenser and a dispensing throat (24) located in the central portion (22). The dispensing throat (24) is composed of a slot portion (26) having a length sufficient to permit a paper napkin to be pulled through by a user, but a relatively narrow width that prevents more than a few napkins from being pulled through the throat (24) at one time. The dispensing throat (24) further includes a finger access portion (28) to help a user grip and pull a paper napkin through the dispensing slot despite the relatively narrow width of the dispensing slot.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakistan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

INTERFOLDED NAPKIN DISPENSING SYSTEM

FIELD OF THE INVENTION

This invention generally relates the field of dispensing devices and systems. More particularly, this invention relates to the field of devices and systems for dispensing folded sheets of material.

BACKGROUND

Dispensers for paper napkins are often provided at quick service food locations. One disadvantage of many conventional paper napkin dispensers is that they often permit removal of large clumps of napkins at one time. Studies have shown most paper napkins removed in this manner are wasted. Many end up scattered about an eating area, tossed as litter or, even worse, being stuffed in plumbing fixtures. When clumps of napkins are taken, dispensers quickly run out and must be refilled inconveniencing both customers and operators of quick service food locations.

A long and unfilled need exists for a paper napkin dispensing system that will deter and resist wasteful dispensing.

SUMMARY OF THE INVENTION

The problems and needs described above are addressed by the present invention which provides an interfolded paper napkin dispensing system composed of: (a) an outer housing defining an interior space; (b) stacking means mounted within the outer housing for holding a stack of paper napkins within the interior space; and (c) a dispensing face defined in the outer housing proximate to an end of the stacking means.

The dispensing face has a central portion projecting out from the dispenser and a dispensing throat located in the central portion. The dispensing throat is composed of a slot portion having a length sufficient to permit a paper napkin to be pulled through by a user, but a relatively narrow width that prevents more than a few napkins from being pulled through the throat at one time. The dispensing throat further includes a finger access portion to help a user grip and pull a paper napkin through the dispensing slot despite the relatively narrow width of the dispensing slot.

According to the invention, the stacking means are composed of a staging area proximate the dispensing throat for spacing, bowing and slowing napkins as they approach the dispensing throat. The staging area may be composed of at least two curved bumpers oriented so as to be parallel to the path of travel of the napkins as they approach the dispensing throat, and a number of ribs defined on the bumpers for

temporarily arresting movement of the napkins as they approach the dispensing throat. Desirably, the staging area and bumpers are configured to cause the napkins to bow out into the dispensing throat.

5 In an aspect of the invention, the slot portion of the dispensing throat may have a point of minimum width that is less than about 1.0 inch. For example, the slot portion of the dispensing throat may have a point of minimum width that is less than about 0.75 inches. As another example, the slot portion of the dispensing throat may have a point of minimum width that is less than about 0.5 inches.

10 According to the invention, the finger access portion of the dispensing throat may have a point of maximum width that is greater than about 0.75 inches. For example, the finger access portion of the dispensing throat may have a point of maximum width that is greater than about 1 inch. Desirably, the finger access portion of the dispensing throat is at the center of the dispensing throat and may have a length (i.e., a length along the dispensing throat) of about 1 inch or more. For example, the finger access portion of the
15 dispensing throat may have a length from about 1 inch to about 3 inches or more. Typically, the finger access portion of the dispensing throat may have a length that is about one-half the length of the dispensing throat. Of course, it is contemplated that the finger access portion of the dispensing throat may have a length that is about one-quarter to about three-quarter the length of the dispensing throat.

20 According to the present invention, the central portion of the dispensing face may project out from the dispenser in the form of a first surface and a second surface joined at an obtuse angle. In such an embodiment, the dispensing throat should be located at about the intersection of the first and second surfaces. Other configurations of the dispensing face which provide a crease or break in the plane of the dispensing face at
25 the dispensing throat may also be used.

These and various other advantages and features of novelty which characterize the invention are pointed out with particularity in the claims annexed hereto and forming a part hereof. However, for a better understanding of the invention, its advantages, and the objects obtained by its use, reference should be made to the drawings which form a
30 further part hereof, and to the accompanying description of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view illustration of an exemplary interfolded napkin dispensing system.

35 FIG. 2 is an illustration of a detail of an exemplary interfolded napkin dispensing system.

FIG. 3 is an illustration of a detail of an exemplary interfolded napkin dispensing system.

FIG. 4 is an illustration of a dispensing throat of an exemplary interfolded napkin dispensing system.

5 FIG. 5 is a perspective view illustration of a dispensing face from an exemplary interfolded napkin dispensing system.

DETAILED DESCRIPTION

Referring now to the drawings, wherein like reference numerals designate
10 corresponding structure throughout the views, and referring in particular to FIGS. 1 and 2, there is shown an exemplary interfolded paper napkin dispensing system. The system includes an outer housing 12 defining an interior space 14 that contains a stacking means 16 which is mounted within the outer housing 12 for holding a stack of paper napkins 18 within the interior space.

15 The system also includes a dispensing face 20 defined in the outer housing 12 proximate to an end of the stacking means 16.

 The dispensing face 20 has a central portion 22 projecting out from the outer housing 12 and a dispensing throat 24 located in the central portion 22. The dispensing throat 24 is composed of a slot portion 26 having a length sufficient to permit a paper
20 napkin to be pulled through by a user, but a relatively narrow width that prevents more than a few napkins from being pulled through the throat at one time.

 The dispensing throat 24 further includes a finger access portion 28 to help a user grip and pull an interfolded paper napkin through the dispensing slot despite the relatively narrow width of the dispensing slot 26.

25 Referring now to FIG. 3, the stacking means 16 are composed of a staging area 30 proximate the dispensing throat 24 for spacing and slowing napkins as they approach the dispensing throat. The staging area 30 may be composed of at least two bumpers 32 oriented so as to be parallel to the path of travel of the napkins as they approach the dispensing throat, and a number of ribs 34 defined on the bumpers 32 for temporarily
30 arresting movement of the napkins as they approach the dispensing throat.

 The bumpers 32, in combination with a spring loaded plate 36 that pushes against the stack of napkins 18, cause the interfolded napkins to bow out or buckle into the dispensing throat 24. Such a configuration is believed to aid dispensing of the napkins by causing the napkins to feed into the dispensing throat 24 relatively uniformly and
35 relatively independent of how full the dispenser is during dispensing. The bumpers also center the napkins on the dispensing throat to reduce the likelihood that napkins will drag

against an end of the dispensing slot creating friction that may tear a napkin and interrupt dispensing. The bow or buckle in the napkins is thought to enhance the contact/friction between interfolded sheets of the paper napkin for more reliable dispensing.

Referring now to FIG. 4, there is shown a detail of the dispensing throat 24 which
5 reveals a configuration to prevent large clumps of paper napkins from being pulled out of the dispenser at one time. Specifically, the dispensing throat 24 has a slot portion 26 that has a length sufficient to permit a paper napkin to be pulled through by a user, but a relatively narrow width that will prevent more than a few paper napkins from being pulled through the throat at one time. The dispensing throat 24 includes a finger access portion
10 28 to help a user grip and pull a paper napkin through the dispensing slot 26 despite the relatively narrow width of the slot.

The slot portion 26 of the dispensing throat 24 may have a point of minimum width "W" that is less than about 1.0 inch. For example, the slot portion "W" of the dispensing throat may have a point of minimum width that is less than about 0.75 inches. As another
15 example, the slot portion "W" of the dispensing throat may have a point of minimum width that is less than about 0.5 inches.

The finger access portion 28 of the dispensing throat may have a point of maximum width "F" that is greater than about 0.75 inches. For example, the finger access portion of the dispensing throat may have a point of maximum width "F" that is greater
20 than about 1 inch.

Desirably, the finger access portion 28 of the dispensing throat 24 is at the center of the dispensing throat and may have a length "L" (i.e., a length along the dispensing throat) of about 1 inch or more. For example, the finger access portion of the dispensing throat may have a length "L" from about 1 inch to about 3 inches or more. Typically, the
25 finger access portion of the dispensing throat may have a length "L" that is about one-half the total length "T" of the dispensing throat. Of course, it is contemplated that the finger access portion of the dispensing throat may have a length "L" that is about one-quarter to about three-quarter the total length "T" of the dispensing throat.

Referring now to FIG. 5, it can be seen that the central portion 22 of the dispensing
30 face 20 projects out from the outer housing 12 of the dispenser. In an embodiment of the invention, the central portion 22 of the dispensing face 20 projects out in the form of a first surface 40 and a second surface 42 joined at an obtuse angle α (i.e., greater than 90 and less than 180 degrees). The dispensing throat 24 should be located at about the
35 intersection 44 of the first and second surfaces 40, 42 where there is a crease or break in the plane of the dispensing face 20. Such configuration is thought to provide better

access to the paper napkins through the relatively narrow dispensing slot 26. It is contemplated that other configurations of the dispensing face which provide a suitable crease or break in the plane of the dispensing face at the dispensing throat may be used.

Generally speaking, the angle α may range from about 175 degrees to about 160
5 degrees to provide a crease or break in the plane of the dispensing face 20. For example, the angle α may range from about 173 degrees to about 162 degrees. As another example, the angle α may range from about 170 degrees to about 165 degrees.

During normal operation, a consumer will grasp the interfolded paper napkin by grabbing the portion or tail of the interfolded napkin protruding/extending through the
10 dispensing slot. As the interfolded napkin is dispensed, another portion of the succeeding napkin is withdrawn to provide the next outwardly extending protruding portion/tail of the napkin. If the consumer encounters a new stack of interfolded napkins in which the tail does not protrude through the dispensing slot 26 or if the previous dispensing failed to properly draw a new tail through the slot, the user will grasp the exposed portion of the
15 paper napkin and pinch the body of the napkin by placing one or more fingers in the finger access portion 28 of the dispensing throat 24. If the user pulls too aggressively, such as in an attempt to pull a large clump of paper napkins out of the dispenser, the attempt will be thwarted because a large clump of napkins will not fit through the dispensing slot 26. Accordingly, wasteful dispensing of the paper napkins is reduced.

20 The present invention had been found to be particularly desirable for use with horizontally placed interfolded paper napkin dispensers. The combination of a narrow dispensing throat, projecting dispensing face, stacking means and bumpers that bow out the napkins in a staging area provide reliable and less wasteful dispensing of interfolded paper napkins.

25 It is to be understood, however, that even though numerous characteristics and advantages of the present invention have been set forth in the foregoing description, together with details of the structure and function of the invention, the disclosure is illustrative only, and changes may be made in detail, especially in matters of shape, size and arrangement of parts within the principles of the invention to the full extent indicated
30 by the broad general meaning of the terms in which the appended claims are expressed.

WHAT IS CLAIMED IS:

1. An interfolded paper napkin dispensing system comprising:
an outer housing defining an interior space;
stacking means mounted within the outer housing for holding a stack of paper
5 napkins within the interior space; and
a dispensing face defined in the outer housing proximate to an end of the stacking
means, the dispensing face having a central portion projecting out from the dispenser
and a dispensing throat located in the central portion, the dispensing throat comprising a
slot portion having a length sufficient to permit a paper napkin to be pulled through by a
10 user, but a relatively narrow width that prevents more than a few napkins from being
pulled through the throat at one time, the dispensing throat further comprising a finger
access portion to help a user grip and pull a paper napkin through the dispensing slot
despite the relatively narrow width of the dispensing slot.
2. The dispenser according to claim 1, wherein the stacking means comprises a
15 staging area proximate the dispensing throat for spacing and slowing napkins as they
approach the dispensing throat.
3. The dispenser according to claim 2, wherein the staging area comprises at
least two curved bumpers oriented so as to be parallel to the path of travel of the napkins
as they approach the dispensing throat, and a number of ribs defined on the bumpers for
20 temporarily arresting movement of the napkins as they approach the dispensing throat.
4. The dispenser according to claim 3, wherein the staging area and bumpers
are configured to cause the napkins to bow out into the dispensing throat.
5. The dispenser according to claim 1, wherein the slot portion of the dispensing
throat has a point of minimum width that is less than about 1.0 inches.
- 25 6. The dispenser according to claim 5, wherein the slot portion of the dispensing
throat has a point of minimum width that is less than about 0.75 inches.
7. The dispenser according to claim 6, wherein the slot portion of the dispensing
throat has a point of minimum width that is less than about 0.5 inches.
8. The dispenser according to claim 1, wherein the finger access portion of the
30 dispensing throat has a point of maximum width that is greater than about 0.75 inches.
9. The dispenser according to claim 8, wherein the finger access portion of the
dispensing throat has a point of maximum width that is greater than about 1 inch.
10. The dispenser according to claim 1, wherein the central portion of the
dispensing face projects out from the dispenser in the form of a first surface and a
35 second surface joined at an obtuse angle, the dispensing throat being located at about
the intersection of the first and second surfaces.

11. An interfolded paper napkin dispensing system comprising:
an outer housing defining an interior space;
stacking means mounted within the outer housing for holding a stack of paper
napkins within the interior space, the stacking means comprising a staging area
5 proximate the dispensing throat for spacing and slowing napkins as they approach the
dispensing throat; and
a dispensing face defined in the outer housing proximate to an end of the stacking
means, the dispensing face having a central portion projecting out from the dispenser
and a dispensing throat located in the central portion, the dispensing throat comprising a
10 slot portion having a length sufficient to permit a paper napkin to be pulled through by a
user, but a relatively narrow width that prevents more than a few napkins from being
pulled through the throat at one time, the dispensing throat further comprising a finger
access portion to help a user grip and pull a paper napkin through the dispensing slot
despite the relatively narrow width of the dispensing slot.
- 15 12. The dispenser according to claim 11, wherein the staging area comprises at
least two curved bumpers oriented so as to be parallel to the path of travel of the napkins
as they approach the dispensing throat, and a number of ribs defined on the bumpers for
temporarily arresting movement of the napkins as they approach the dispensing throat.
- 20 13. The dispenser according to claim 12, wherein the staging area and bumpers
are configured to cause the napkins to bow out into the dispensing throat.
14. The dispenser according to claim 11, wherein the slot portion of the
dispensing throat has a point of minimum width that is less than about 1.0 inches.
15. The dispenser according to claim 14, wherein the slot portion of the
dispensing throat has a point of minimum width that is less than about 0.75 inches.
- 25 16. The dispenser according to claim 15, wherein the slot portion of the
dispensing throat has a point of minimum width that is less than about 0.5 inches.
17. The dispenser according to claim 11, wherein the finger access portion of the
dispensing throat has a point of maximum width that is greater than about 0.75 inches.
18. The dispenser according to claim 17, wherein the finger access portion of the
30 dispensing throat has a point of maximum width that is greater than about 1 inch.
19. The dispenser according to claim 19, wherein the central portion of the
dispensing face projects out from the dispenser in the form of a first surface and a
second surface joined at an obtuse angle, the dispensing throat being located at about
the intersection of the first and second surfaces.

1/3




FIG. 1




FIG. 2

2/3




FIG. 3




FIG. 4

3/3




FIG. 5

INTERNATIONAL SEARCH REPORT

In. ational Application No

PCT/US 97/21373

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 A47K10/42 A47K10/44

According to International Patent Classification(IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 A47K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 3 203 586 A (C. E. DOWNHAM) 31 August 1965 see the whole document ---	1,2, 10-12,19
X	US 5 076 466 A (T. PETTERSON ET AL.) 31 December 1991 see the whole document ---	1
A	FR 336 986 A (A. E. SEXTON) 22 March 1904 see the whole document ---	1-4, 11-13
A	US 4 679 703 A (R. F. DE LUCA) 14 July 1987 see the whole document ---	1-4, 11-13
-/--		

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

10 March 1998

Date of mailing of the international search report

24/03/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Delzor, F

INTERNATIONAL SEARCH REPORT

International Application No
PCT/US 97/21373

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	FR 1 016 522 A (A. VIVIANI) 14 November 1952 see the whole document -----	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 97/21373

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 3203586 A	31-08-65	NONE	
US 5076466 A	31-12-91	CA 2062585 A EP 0506243 A	13-09-92 30-09-92
FR 336986 A		NONE	
US 4679703 A	14-07-87	CA 1243639 A	25-10-88
FR 1016522 A	17-11-52	NONE	